

FX5202 - For DIN Rail

AMD Geode LX-800 Small System with VGA, 2S, 1 LAN, 2 USB, Audio and CF



Features

- Fanless and low power consumption design
- One PS/2 KB/MS
- 256MB DDR-DRAM inside
- One VGA
- One LAN (10/100 base TX)
- 2USB(V2.0)
- One CompactFlash slot
- One 2.5" Hard disk space
- 4 LED Indicators (Power, CF/HDD, LAN)

Specifications

CPU Board: AMD Geode LX-800 Lower Power CPU board with 256MB DDR SDRAM inside
One So-DIMM socket up to 1GB DDR-DRAM

I/O Outlets: 2 Serial Port (RS-232)
1 PS/2 Keyboard/Mouse
2 USB (2.0)
1 CRT
1 Mic-in and 1 line-Out Audio Connector
1 Terminal Block for DC power input with Power switch
1 LAN (10/ 100BASE-TX)
1 push button reset switch

Storage Bay: One 2.5" HDD space, and 1 CompactFlash slot.

LED Indicators: 1 power LED , 1 HDD/CF access LED, 2 LAN LEDs.

Power Req.: DC 12 - 24V, 11VA maximum With 2.5" HDD and 24V input vlotage.

Operating Temperature: 0~50 degree C. (32~122 degree F.)

Dimensions: 123.0mm (H) x 120.0mm (D) x 44.0 mm (W)

Accessory: CBL-KB+MS-Y type keyboard and mouse adapter cable
1 Din Rail mounting kit with 3 screws.
1 2-pin apartable terminal block.
1 44-pin flat cable and 4 screws for fixing and connecting a 2.5" hard disk drive.

Order Information

Model	Description	Drivers
FX5202	AMD Geode LX-800 Embedded System with LAN, 4USB ports, 2COM Ports and 256MB DDR RAM.	* VGA/Audio: WinXP/2K, Linux * LAN Novell 3.X / 4.X Win95/98/NT, OS2, Linux NDIS, MSLAN