

TkThick X7-2LS



- ▶ Fanless design
- ▶ VIA Eden Esther 1.2GHz
- ▶ 512MB DDR2
- ▶ MPEG4/WMV9 decoding accelerator
- ▶ Dual LAN
- ▶ Compact Flash slot

- ▶ 2 x USB 2.0 ports
- ▶ Support 2.5" HDD
- ▶ PXE diskless boot

Specification

4853S

System	
CPU	VIA Eden Esther 1.2GHz processor
BIOS	AMI BIOS
System Chipset	VIA CX700M
I/O Chip	Winbond W83697
System Memory	Onboard 512MB DDR2
I/O	
MIO	1 x EIDE (UltraDMA 133) 1 x PS/2 K/B, 1 x PS/2 Mouse
USB	1 x RS-232
Compact Flash slot	2 x USB 2.0 Ports (one in front) Type I/II Compact Flash slot
Display	
Chipset	Integrated VIA UniChrome Pro II, 2D/3D Graphics with MPEG4 and WMV9 decoding accelerator
Display Memory	Up to 128 MB share system memory
Resolution	Up to 1920 x 1440
Audio	
AC97 2.2(Codec)	VIA Vinyl VT1708
Audio Interface	Mic In, Line Out
Ethernet	
Chipset	Realtek RTL8100B 10/100 Base-T Ethernet
Chipset (2 nd)	Realtek RTL8100B 10/100 Base-T Ethernet
Remote Boot ROM	built-in boot ROM function
Mechanical & Environment	
Power Requirement	+5V @ 4A
Operating Temp	0 ~ 60°C
Operating Humidity	0% - 90% relative humidity, non-condensing
Size (W x H x D)	170 x 123 x 56 mm
Weight	970 g
Certification	CE, FCC

Note • The specification is subject to change without prior notice.

